

C95225899

C95-P



C95-P240x1200 20/80 GR 4000 HF 840 PRE C2 MP

EAN-nr: 7332402258998

Stock code: B

GlamoX C95 is a family of high end interior luminaires. The family is characterized by a clean, minimalistic design and fully illuminated surfaces.



Electrical data	
Voltage from (V)	220
Maximum voltage (V)	240
Minimum frequency (Hz)	50
Maximum frequency (Hz)	60
Total consumption (W)	25
Number of luminaires on a 10A MCB type B (80% load)	11
Number of luminaires on a 10A MCB type C (80% load)	19
Number of luminaires on a 16A MCB type B (80% load)	19
Number of luminaires on a 16A MCB type C (80% load)	31
Leakage Current (mA)	0,5
Dimensions	
Net weight (kg)	8,1
Gross weight (kg)	8
Length (mm)	1194
Width (mm)	234
Height (mm)	42
Optic	
Optic	MP = Micro-Prismatic
Material of diffuser	Acrylic
Lightdistribution Up/Down	20/80
Body	
Body material	Aluminium
Colour of body	Anodized

Light technical data	
Light source	LED
Colour rendering and colour temperature	CRI >80, 4000K
Lumen Out	4009
MacAdam step	3
Lumen/Watt	160
Median useful life (EN 62717) Ta25	100000h L90B50
Luminous flux decline (LLMF) 50000h Ta25	0.95
L90B50 Median useful life (EN 62717) Ta25 (hr)	100000
Termination	
Termination	3x2x2,5 ² push-in
Cable length (m)	2
Mounting Accessories	Premounted suspension
Ballast	
Type of Ballast	HF = High frequency
Number of ballast	1
Technical data	
IP classification	40

C95225899

C95-P

Drawings

